

# LINEAR SERIES



DATE PROJECT

COMMENTS

CERTIFICATIONS



## 5S SUSPENDED DIRECT

AN EXTENSION OF OUR 5-INCH LINEAR FAMILY SERIES

### FEATURES

#### OPTICAL SYSTEM

- 1. VERSATILE LIGHT ENGINE**  
Multiple lumen intensities provide the correct level of illumination within each space.
- 2. EVENLY ILLUMINATED DIRECT LENS**  
High efficiency diffuser designed to minimize glare and provide uniform light distribution.

#### HOUSING

- 3. HIDDEN CONNECT**  
Semi-recessed connection point between cable and fixture reduces the visibility of hardware.


#### 4. SURE-FIT ALIGNMENT

4-Point alignment system adjoining each luminaire section to ensure straighter rows while minimizing the appearance of seams.


#### ELECTRICAL

- 5. OPTIONAL INTEGRAL EMERGENCY BATTERY PACK**  
UL Listed 924 emergency system has been engineered to exceed UL minimum safety standards.
- 6. 0-10 VOLT DIMMING STANDARD**  
120/277VAC 0-10V dimming to 1% standard.

LIGHT DISTRIBUTION



CROSS-SECTION



### ORDERING

SERIES	LENGTH	OUTPUT	CCT	VOLTAGE	MOUNTING	FINISH
5S	XXX FT	VHD 1250 LM/FT	LD 500 LM/FT	30 3000K UNV 120-277V	T1 1" T-Grid	HC Hard Ceiling
	2' Increments Ex: 20' = 20	HD 1000 LM/FT	VLD 250 LM/FT	35 3500K 347 <sup>1</sup> 347V	T9 9/16" T-Grid	JB Junction Box
		MD 750 LM/FT	CD Custom	40 4000K	SC Screw Slot Grid	
<b>ORDERING NOTES</b>						
1 EM not available with 347V.						
2 EM not available with 2' fixtures.						
<b>FINISH</b>						
						WH White
						BLK Black
						S Silver
						GR CHARCOAL Gray

### OPTIONS

CRI	SUSPENSION	INTEGRATED CONTROLS	FOR INDIVIDUALS	FOR LINEAR RUNS <sup>3,4</sup>
BLANK = 80 CRI	BLANK = 48" CABLE	OS Occupancy Sensor	EM <sup>2</sup> Emergency Battery	EM EMERGENCY BATTERY PACK
C90 90 CRI	CB96 96" Cables	DOS Daylight Occupancy Sensor	EC Emergency Circuit	EC EMERGENCY CIRCUIT
	CB144 144" Cables			QUANTITY PER RUN <sup>3</sup>
	BC Black Canopy & Cord			POSITION IN RUN <sup>4</sup>

#### EMERGENCY OPTION NOTES


3 EM and EC Quantity is not to exceed number of discrete fixture sections in a row.

4 EM and EC position refers to which fixture in the run that will be powered by the EM/EC circuit.  
Position Options: S=Starter, J=Joiner, E=Ender  
Ex: 5S-24-HD-35-UNV-T1-WH-EM2SJ



# 5S SUSPENDED

## DIRECT




### PHOTOMETRICS & ENERGY CHARTS

#### 5S-04-HD-35-UNV-XX-X

Total Lumens: 4,090  
 Ratio: 0% Up and 100% Down  
 Wattage: 29.3  
 Efficacy: 139.4 LM/W  
 Fixture Length: Four Feet

#### Zonal Lumen Summary

Zone	Lumens	% Fixt
0 - 30	1164.1	28.5
0 - 40	1876.7	45.9
0 - 60	3233.9	79.1
0 - 90	4089.6	100.0
90 - 180	0.58	0.0
0 - 180	4090.2	100.0



#### Coefficients Of Utilization

RC	80				70				50			
	RW	70	50	30	10	70	50	30	10	50	30	10
0	119	119	119	119	116	116	116	116	111	111	111	
1	109	104	100	96	106	106	98	94	97	94	91	
2	99	91	84	78	96	96	82	77	85	80	75	
3	90	80	71	65	88	88	70	64	75	69	63	
4	83	71	62	55	80	80	61	55	67	60	54	
5	76	63	54	47	74	74	53	47	60	52	47	
6	70	57	48	41	68	68	47	41	54	47	41	
7	65	52	43	37	63	63	42	36	49	42	36	
8	61	47	39	33	59	59	38	33	45	38	32	
9	57	43	35	29	55	55	35	29	41	34	29	
10	53	40	32	27	52	52	32	27	38	31	27	

#### Watts Per Linear Foot

	H2:1200	H1:1000	H:800	M:600	L:400
Watts/ft	12.2	9.1	7.7	5.7	4.1
Lumens/ft	1370.3	1071.5	879.3	659.8	448.8
LPW	112.5	117.4	114.4	116.3	110.8

### SPECIFICATIONS

## MECHANICAL

### Housing Construction:

Extruded Aluminum 6063-T5 alloy outer housing with die-formed steel internal components for strength, alignment and mounting attachment. Our high-quality die-cast end caps are engineered to conceal all fasteners and to retain the sealing gaskets on the inside of the fixture while completing the clean and minimalistic look of this luminaire.

### Alignment/Assembly:

The alignment system employs a six-point alignment and attachment method, designed to create straighter rows and minimize seams between sections (field assembled). Four alignment pins ensure the outer extruded aluminum rails are aligned, two extended biscuits provide additional strength and a light shield, while two vertical draw-screws secures housing-to-housing attachment.

### Lengths:

The 5S is available in a minimum 2-foot (nominal) length with additional 2-foot increments available. Longer fixture rows are available and will be configured per Lumato factory specifications; typical rows are configured with 4-foot, 6-foot and 8-foot fixtures. Max run length on one power feed is 72'. Continuous runs over 72' will require 2 power feeds.

### Mounting Method/Hardware:

Standard hanging hardware includes 1/16" diameter, galvanized steel aircraft cable with adjustable and lockable nickel-plated cable grippers and a white 18/5 S.J.T. power cord. The standard hardware includes a 60" power cord and 54" aircraft cables to accommodate a 48" mounting distance from the ceiling. Ceiling canopy provided. All suspension hardware is tested and listed to UL 1598 requirements for loading/fixture support.

### Exterior Finish:

The 5S is available in White and Black polyester powder coat finish to ensure durability.

### Suspension Components:

Fixtures are suspended by 1/16" galvanized aircraft cable. Cables are attached to the ceiling suspension point with a 1/4-20 threaded ceiling cable barrel that incorporates a threaded ring to support the feed/hanger canopy allowing access to the j-box/hanger without removal of the suspension cable allowing conductor inspection/service without having to support the fixture(s). Feed canopies are 5" O.D. and hanger canopies are 2" O.D. Cable lengths can be specified for 48", 96" and 144" suspension lengths. Ceiling type options are "T1" T-Grid, "T9" T-Grid, "SC" screw slot grid, "HC" hard ceiling or "JB" hard ceiling j-box mount.

### Integrated Controls:

The 5S is available with optional integrated controls. Sensors are conveniently designed to mount in aperture and are located at the power feed end of each fixture. For runs, each fixture section will be supplied with a discrete sensor that will control that specific section.

## OPERATION

### Light Engine:

The 5S is available in 3000K, 3500K and 4000K CCT all within a 3-Step MacAdam Ellipse and has a standard CRI of 80+. Optional 90+ CRI available.

### Optics:

The back lit extruded acrylic lens ensures high efficiency light output, in a minimal form factor for a clean, evenly illuminated lower surface with minimal glare.

### Electrical:

Class 2 programmable (factory pre-set) premium power supply, 120-277VAC input. Power factor >0.9. THD <15%. Integral Surge Protection to 2KV.

### Dimming:

The 5S comes standard with 0-10V dimming down to 1%.

### Emergency Battery Pack:

UL Listed 924 Emergency System has been engineered to exceed UL Minimum Safety Standards. For most fixtures, the entire direct portion of the fixture will be illuminated by the EM Battery Pack. For 8' VHD, 10' HD and VHD, and 12' MD, HD, and VHD, only the first portion of the fixture will be illuminated by the EM battery pack. "Quantity per Run" refers to the number of fixtures in the run that will be supplied with an emergency battery pack. "Position in Run" refers to which fixture in the run that will contain the battery. Position options are Starter (S), Joiner (J), or Ender (E). For example, a 24' run needing two emergency battery packs, one in the starter and one in the joiner, would be ordered as EM2SJ. When a joiner is selected, battery packs are always supplied in 8' fixtures before 6' fixtures in that run.

### Emergency Circuit:

Emergency Circuit fixtures are engineered so that the entire fixture is wired to the emergency circuit. "Quantity per Run" refers to the number of fixtures in the run that are wired to the emergency circuit. "Position in Run" refers to which fixture in the run that will be powered by the Emergency Circuit. Position options are Starter (S), Joiner (J), or Ender (E). For example, a 24' run with needing two emergency sections, one in the starter and one in the joiner, would be ordered as EC2SJ. When a joiner is selected, Emergency Circuits are always supplied in 8' fixtures before 6' fixtures in that run.

## GENERAL

### Warranty:

Five (5) Year limited warranty from date of shipment.

### Lumen Maintenance:

Rated for 85% initial lumen output at 85,000 Hours of operation, operated at 25°C ambient temperature; per TM-21 Guidelines published by the Illuminating Engineering Society (IES).

### Certifications:

All luminaires are UL/cUL Listed to UL 1598 Standards and approved for Indoor use in Dry/Damp Locations.

### Shipping:

2-Week lead time for orders up to 1000 Linear Feet.  
 4-Week lead time for orders with a Black finish.  
 Lead time for orders greater and 1,000' will be determined at time of order.

### Manufactured in the USA:

All Lumato Luminaires and Components (with the exception of our LED boards and drivers) are proudly manufactured and assembled in the USA.